

JTMill 2Flutes Carbide Square Endmill

超硬2枚刃スクエアエンドミル



汎用性の高い30°ねじれエンドミル
性能が高く価格のメリットも大

MicroGrain



刃径公差	+0,-0.02
シャンク公差	h6

型番	刃径	刃長	全長	シャンク径	
2JT100	1	2.5	40	4	
2JT150	1.5	4	40	4	
2JT200	2	6	40	4	
2JT250	2.5	8	40	4	
2JT300	3	8	45	6	
2JT400	4	11	45	6	
2JT500	5	13	50	6	
2JT600	6	13	50	6	
2JT800	8	19	60	8	
2JT1000	10	22	70	10	
2JT1200	12	26	75	12	

切削条件

溝切削

被削材	炭素鋼		工具鋼		調質鋼	
	鋳鉄		合金鋼			
硬さ	~ HRC30		HRC30 ~ 40		HRC40 ~ 50	
刃径	回転数	送り	回転数	送り	回転数	送り
	(rpm)	(mm/min)	(rpm)	(mm/min)	(rpm)	(mm/min)
1	14,000	120	12,000	90	10,700	60
1.5	14,000	120	12,000	90	10,700	60
2	9,250	190	6,050	120	4,030	30
2.5	9,250	190	6,050	120	4,030	30
3	7,150	210	4,450	140	2,350	40
4	6,050	300	3,700	180	2,350	40
5	5,050	320	3,020	190	1,860	50
6	4,450	350	2,690	220	1,350	75
8	3,360	380	2,020	200	1,350	75
10	2,600	330	1,600	160	1,090	60
12	2,200	280	1,350	130	930	55
切り込み量	<p>Aa : 0.5D (D≥3) 0.2D (D<3)</p>				Aa : 0.05D	



エスアンドケー-SALES 株式会社

〒124-0025 東京都葛飾区西新小岩4-8-12
TEL.03-5671-2050 FAX.03-5698-8117